



Material Safety Data Sheet

Printed Date: 05/01/2011

Manufacturing & Supply, Inc.
PO Box 2659
White City, Oregon 97503 USA

Emergency Phone No. 541-826-5211
FAX No. 541-826-8669

Section I. Identification

Trade Name: Corbin Swage Lube

HMIS/NFPA Hazard Identification System:

Health: 0

Flammability: 1

Threshold Limit Value (TLV):

Reactivity: 0

Protective Code: A

No TLV has been established for this product.

Section II: Hazardous Ingredients

None

Section III: Physical Data

Boiling Point: N/A

Evaporation Rate: Slower than ether

Density (lb/gal): 8.3

Vapor Density: Heavier than air

% Volatile by Volume: NIL

Solubility in Water: 0% by wt. @ 20° C.

Section IV: Fire and Explosion Hazard Data

D.O.T. Category: Not Regulated

Flash Point: 540°F.

Extinguishing Media: Foam, carbon dioxide, dry chemical

Unusual Fire and Explosion Hazards: None

Section V: Reactivity Data

Stability: Stable

Conditions to avoid: Keep from contact with oxidizing materials.

Hazardous Decomposition Products: Products of incomplete combustion can include CO, CO₂ and dense smoke.

Section VI: Health Hazard Data

Effects of overexposure: Prolonged exposure may cause skin and eye irritation.

Emergency & First Aid Procedures: Eyes - flush with plenty of water. Skin - wash with soap and water.

Section VII: Spill or leak procedures

Spill clean-up procedure: Take up spill with sand, earth, sawdust, or other adsorbant. Flush spill area with detergent and water.

Waste disposal method: Dispose of in accordance with state, local and federal regulations, as you would with any bio-degradable organic fat or oil

Section VIII: Special Protection Information

Respiratory protection: No special respiratory protection is required under normal conditions.

Ventilation: No special ventilation is required.

Protective gloves: Chemical resistant gloves should be worn for prolonged exposure.

Other protective equipment: Safety shower and eye wash station should be provided.

Section IX: Special Precautions

Precautions to be taken in handling and storing: Store in closed containers, preferably at temperatures below 120°F and above 32°F. Freezing has no apparent effect on the utility of the product but may cause bursting of the containers from expansion. Prolonged storage at high temperature may cause separation or partial liquification of components, which should then be remixed at 120-150°F and cooled to room temperature before using. Protect from contamination with foreign materials.

Other precautions: Do not transfer into unmarked drums.